


US Industrial Sourcing, L.L.C.

Hose - Stainless Steel Braided

HSS Series



PRODUCT DESCRIPTION: The USIS Model HSS is a stainless steel hose that is braided for corrosion resistance. The flexible hose eases installation in hot or cold applications. The HSS has GRIP-MATE couplings for better connections and fully crimped ferrule for stronger coupling retention.

PRODUCT SPECIFICATIONS	
Tube	Engineered Polymer Rubber - SAE J1019 (½" - 1") and SAE 20R1-D1 (1-¼" - 2")
Reinforcement	304L Stainless Steel braid cover meets UL-94 requirements
Couplings	½" - 1" Sizes: Solid brass hex tapered NPT male and integral swivel male NPT termination with stainless steel ferrules 1-¼" - 2" Sizes: Plated steel male NPT with plated steel ferrules.
End Fittings	½" - 1" I.D. - Brass 1-¼" - 2" I.D. - Steel
Temperature	-40°F to +212°F / 225°F Intermittent

Model #	Length	Size	Working PSI	Static Burst PSI	Bend Radius
HSS112	12"	½"	400 PSI	1600 PSI	5"
HSS212	12"	¾"	400 PSI	1600 PSI	7"
HSS312	12"	1"	400 PSI	1600 PSI	7"
HSS412	12"	1-¼"	300 PSI	1600 PSI	8"
HSS118	18"	½"	400 PSI	1600 PSI	5"
HSS218	18"	¾"	400 PSI	1600 PSI	7"
HSS318	18"	1"	400 PSI	1600 PSI	7"
HSS418	18"	1-¼"	300 PSI	1600 PSI	8"
HSS518	18"	1-½"	300 PSI	1600 PSI	9"
HSS618	18"	2"	300 PSI	1600 PSI	10"
HSS124	24"	½"	400 PSI	1600 PSI	5"
HSS224	24"	¾"	400 PSI	1600 PSI	7"
HSS324	24"	1"	400 PSI	1600 PSI	7"
HSS424	24"	1-¼"	300 PSI	1600 PSI	8"
HSS524	24"	1-½"	300 PSI	1600 PSI	9"
HSS624	24"	2"	300 PSI	1600 PSI	10"
HSS130	30"	½"	400 PSI	1600 PSI	5"
HSS230	30"	¾"	400 PSI	1600 PSI	7"
HSS330	30"	1"	400 PSI	1600 PSI	7"
HSS430	30"	1-¼"	300 PSI	1600 PSI	8"
HSS530	30"	1-½"	300 PSI	1600 PSI	9"
HSS630	30"	2"	300 PSI	1600 PSI	10"
HSS136	36"	½"	400 PSI	1600 PSI	5"
HSS236	36"	¾"	400 PSI	1600 PSI	7"
HSS336	36"	1"	400 PSI	1600 PSI	7"
HSS436	36"	1-¼"	300 PSI	1600 PSI	8"
HSS536	36"	1-½"	300 PSI	1600 PSI	9"
HSS636	36"	2"	300 PSI	1600 PSI	10"